



- DEDICATED PROFESSIONAL SUPPORT
- AN EXTENSIVE PORTFOLIO TO CHOOSE FROM
- FREE ONLINE INFORMATION RESOURCE
- QUICK & EFFICIENT SERVICE

PRODUCT INFORMATION

TEVERE RANGE INFORMATION



Floor Tile: **TEVERE COLOUR: 02**

Disclaimer: The various finishes and sizes shown are not necessarily available in all colours. For specific information on size, finish and colour availability, please contact a PROSPEC representative.

Colours Available



Sizes Available:

100x600mm, 300x300mm, 300x600mm, 450x450mm, 600x600mm, mosaic

Finishes Available:

Natural (Matt) Finish: Slip Resistance Rating = R9
 Bush Hammered Finish: Slip Resistance Rating = R11 (Barefoot Rating 'B')
 Semi-polished Finish: Slip Resistance Rating = N/A
 Polished Finish: Slip Resistance Rating = N/A



AT A GLANCE

Product Type

Unglazed Porcelain Stoneware

Finishes and Suitability

Finishes Available

Natural (Matt), Bush Hammered, Semi-polished, Polished

Natural (Matt) Suitability

Interior/Exterior use for Walls & Floors

Bush Hammered Suitability

Interior/Exterior use for Walls & Floors

Semi-polished Suitability

Interior Floors Only. Interior/Exterior Walls

Polished Suitability

Interior Floors Only. Interior/Exterior Walls

Areas of Use - Product Suitability

Domestic

Kitchens, bathrooms, conservatories, etc

YES

Residential

Hotels, housing, etc

YES

Public Areas - Light

Restaurants, offices, shops, etc

YES

Public Areas - Heavy

Shopping Centres, supermarkets

YES

Commercial

Airports, high density traffic areas, etc

YES

Industrial

Heavy Industrial Areas

NO



THE ESSENTIAL RESOURCE
 FOR CONTRACT TILE
 SPECIFICATION

For more information or to order a sample,
 please call **0115 939 5903**

or visit www.prospectiles.com

Slip Resistance

Natural (Matt) Finish: Slip Resistance Rating	= R9
Bush Hammered Finish: Slip Resistance Rating	= R11 (Barefoot Rating 'B')
Semi-polished Finish: Slip Resistance Rating	= N/A
Polished Finish: Slip Resistance Rating	= N/A

Surface Hardness

Natural (Matt) Finish: MoHs Rating	= 7-8 (Conforms)
Bush Hammered Finish: MoHs Rating	= 7-8 (Conforms)
Semi-polished Finish: MoHs Rating	= N/A (Conforms)
Polished Finish: MoHs Rating	= N/A (Conforms)

Water Absorption

All Finishes: (less than) <0.1% (Conforms)

Acid & Alkali Resistance

All Finishes: Resistant (acc to test criteria) (Conforms)

Thermal Shock Resistance

All Finishes: Resistant (acc to test criteria) (Conforms)

Frost Resistance

All Finishes: Resistant (acc to test criteria) (Conforms)

Deep Abrasion Resistance

All Finishes: (less than) <150mm³ (Conforms)

Bending Strength

All Finishes: 40 – 55 N/mm² (Conforms)

TEST STANDARDS

DIN 51130
()=DIN 51097

EN 101

EN 99

EN 106

EN 104

EN 202

EN 102

EN 100

TEVERE SERIES

This range is inspired by the translation of the materials, surfaces and harmonic structures of the mineral world into technological products.

State-of-the-art production guarantees exclusivity of design.

With four separate surface finishes and realising the aesthetic of seven stratified natural stones, the range characterises the essence and identity of natural stone. The range is rectified, allowing for an almost seamless floor finish.

An inspired collection for modern residential or commercial living.

A series of decorative/special pieces accompanies this range. Please enquire for details.

